



REV.	DESCRIPTION	DATE
A		
B		10-2009




Coax Cable Specifications:

RG59 75 Ohm Coaxial Cable
 20AWG 0.82mm Solid Bare Copper Center Conductor
 16/8/0.12mm CCA Braid (95% Coverage)
 3.66mm OD PE Dielectric
 6.1mm OD Black PVC Jacket



Power Cable Specifications:

2 x 18AWG Bare Stranded Copper Center Conductor
 Black and Red PVC Conductor Jackets
 Insulation OD: 2.8+/-0.2mm
 CM, 30V, 70C



PART NO.	CABLE LENGTH
10X3-18291NF	500 ft
10X3-18291NH	1000 ft

ITEM NUMBER	10X3-18291Nx		DRAWER	LIBRA
TITLE	RG59 Siamese Solid Coaxial Cable + 18/2 (18AWG 2C) Power, White, Spool		CHECKED	
MATERIAL	SCALE		APPROVED	
REV.	A	UNIT	INCH	

2	18AWG Bare Stranded Copper Center Conductor, Insulation OD: 2.8+/-0.2mm, CM, 30V, 70C, Black and Red PVC Jackets
1	RG59 Cable, CM, 75Ohm with 95% CCA Braided Shield, White Outer PVC Jacket.
NO.	SPECIFICATIONS
	BOM LIST

